



Reyton Fully Synthetic SAE 5W-40

Passenger Car Motor Oil

Product Data Sheet



PRODUCT DESCRIPTION

Reyton Fully Synthetic SAE 5W-40 is an advanced fully synthetic motor oil designed and formulated to ensure ultimate engine protection with reduces fuel consumption. With the addition of turbo and nos additives, it ensures a smooth and high power output throughout your driving experience. Reyton Fully Synthetic SAE 5W-40 meets or exceeds the requirements of various manufacturers and industry standards which outperforms conventional oils.

BENEFITS

- Maximum power and performance
- High thermal and oxidation stability to preserves and protects engines providing maximum engine life
- Reduced emissions
- Reduces fuel consumption
- Cleaner engine

FEATURES

Reyton Fully Synthetic SAE 5W-40 is a multigrade gasoline engine oil formulated with fully synthetic oils and special racing additives for use in passenger car and light truck engines requiring SAE 5W-40 viscosity or API SN to provide maximum performance. Specifically tailored viscosity characteristics and effective friction modifier minimize internal engine frictional losses.

APPLICATIONS

- Naturally aspirated and turbocharged gasoline engines in passenger cars where SAE 5W-40 viscosity API SN or earlier API "S" performance categories are specified.
- Light truck gasoline engines where SAE 5W-40 viscosity API SN or earlier API "S" performance categories are specified.
- Low emission passenger cars and light duty vehicle engines fitted with latest catalytic converter or diesel particle filler technology.

MEETS OR EXCEEDS STANDARDS

- API SN (licenced)
- ACEA: A3/B4

TESTS	RESULTS
SAE Grade	5W-40
Viscosity Index	170.263
Kinematic Viscosity	
@40°C, cSt (ASTM D445)	93.660
@100°C, cSt (ASTM D445)	15.112
Phosphorous (ASTM D4951)	0.07
Flash Point, °C (ASTM D92)	220
Pour Point, °C (ASTM D97)	-38
Total Base Number (ASTM D2896)	8.5
Density, g/ml (ASTM D4052)	0.851

This information was prepared in good faith from the best information available at the time of issue.
While the values and characteristics are considered representative, some variation, not affecting performance, can be expected.
It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.